



REF. ADS **02.00**

ACCESSORIES | **HYDRAULIC LIGHTING TOWER**

Available only under request for PRAMAC Generating Sets of the range GBL 20-30-40.

- Suitable for Rental and Public Works, shows and social acts.
- 6 x 1.500W halogen lamps.
- Connection of lamps by CE sockets.
- 200.000 lumen lighting capacity .
- Site trailer with four Site trailer with 4 support feet.
- Hydraulic lifting.
- Electric engine, hydraulic devices and control for tower lifting.
- Telescopic tower with an extension of 7,5 metres (max. 9m)
- Galvanized mobile unit (site trailer).



- Multi-Directional lighting system by quartz/iode lamps (halogen type).
- 6 x 1.500W lamps with a consumption of 12kVA.
- Lighting capacity 200.000 lumen very suitable for large surface lighting.
- Halogen lamps characterized by: intense, solar and long light.
- Protection level IP55.



- Lighting supply by CE sockets. Check the GBL Data Sheet for more details.
- IP45 panel as place to protect both tower and lighting circuit breaker protection.
- Easy and quick connection between genset and lights by means of multi-pin connector.
- Manual turning up to 355° degrees by means of flywheel.
- Mechanical block to avoid the tower turning when it is being used by the effects of wind.
- Electric engine to move all hydraulic devices.
- Hydraulic tower control by handle commands and easy operation.
- Dual safety control system.



- Telescopic tower with a maximum extension of 9 metres (recommended: 7,5m).
- Searchlights connection by retractile cable, inserted in a protective tube.
- Quick fixation to the site trailer to do easier the movement of the generating set.
- Local for lights placement once they have been removed from the tower.
- FRAME: made of galvanized high quality steel for a maximum loading of 1.800kg.
- SITE TRAILER: 1 axle, 2 wheels, hook-eye, jockey wheel and 4 telescopic supports as feet for adjustable height and reduction of risks by overturning.



TECHNICAL CHARACTERISTICS NOT IMPEGNATIVE RESERVATION OF MODIFICATIONS FOR INNOVATION OF THE PRODUCT

TECHNICAL CHARACTERISTICS NOT IMPREGNATIVE RESERVATION OF MODIFICATIONS FOR INNOVATION OF THE PRODUCT



DIMENSIONS AND WEIGHT:

Length:	4.450 mm.
Width:	1.520 mm.
Height:	2.080 mm.
Weight:	760 kg (Generating Set not included).

Note: Minimum dimensions.